

1-PIECE BALL VALVE
 BAR STOCK / INVESTMENT CASTING
 ASTM A 351 CF8M / ASTM A 216 WCB

1H2K TYPE

FEATURES:

- PIPE THREAD IN ACCORDANCE WITH:
 - * ANSI B2.1 (BASIC STD FOR STEEL PIPE THREADS)
 - * ANSI B1.20 (NPTF)
 - * BS21:1973
 - * DIN259/2999
 - * ISO228
- BLOW-OUT PROOF STEM
- REDUCE BORE
- 2000 PSI W.O.G
- MATERIAL TRACEABILITY
- MATERIAL:
 - * ASTM-A351-CF8, ASTM-A351-CF8M, A216-WCB
- OPTION: POLISHED SURFACE (SST ONLY)

DIMENSIONS		UNIT:mm				
	SIZE	PORT	L	E	H	W
DN8	1/4"	5.0	39.0	70.0	30.5	17.0
DN10	3/8"	7.2	44.0	81.5	31.0	21.0
DN15	1/2"	9.2	56.5	97.0	47.0	25.0
DN20	3/4"	12.5	59.0	97.0	51.0	32.0
DN25	1"	15.0	71.0	101.0	52.0	38.0
DN32	1-1/4"	20.0	78.0	101.0	57.0	48.0
DN40	1-1/2"	25.0	83.0	146.0	66.5	53.0
DN50	2"	32.0	98.0	146.0	71.5	64.0

PARTS		MATERIAL	
1	BODY	A216-WCB	ASTM-A351-CF8M
4	BALL	ASTM-A351-CF8M	
5	STEM	ASTM-A351-CF8M	
9	INSERT	ASTM-A351-CF8M	
11	BODY SEAL	PTFE	
12	SEAT	15% G/F + R-PTFE	
13	THRUST WASHER	PTFE	
14	STEM PACKING	PTFE	
15	GLAND WASHER	ASTM-A351-CF3	
19	HANDLE	ASTM-A351-CF3	
21	HANDLE COVER	PLASTIC (VINIL GRIP)	
23	SPRING WASHER	ASTM-A351-CF3	
24	HANDLE NUT	ASTM-A351-CF3	



SIZE: 1/4" - 2"
 1 PIECE
 SCREWED END
 CE APPROVED

HOW TO ORDER

BODY MATERIAL SIZE END CONNECTIONS
 1H2K R3T

